

Deneva 2 R Series Storage Solutions



Deneva 2 SATA 3.0 Solid State Drives – 2.5" SLC

R Series at a Glance

- Leading-edge SATA 6Gb/s storage solution designed to dramatically increase productivity & application performance
- Cost-effective SLC-based design with best-in-class endurance & reliability
- Advanced feature-set includes power loss data protection

Raising the Bar in Performance

- Nearly double the speed of the previous generation
- Delivers the performance of hundreds of hard disk drives in a single server
 Over 500MB/s of throughput
 - Up to 80,000 4K random write IOPS

Reliable, Longer-Lasting, & Secure

- Data fail recovery ensures superior reliability
- Maximized product lifespan with write amplification as low as 0.2
- Intelligent block management & wear-leveling for increased endurance
- Advanced security with 128-bit AES encryption support
- Strong error correction for enhanced data integrity

Flexible Design with a Wide Array of Configurations

• Deneva 2 comes in an industry-standard 2.5" model; however, its unique architecture can be tailored to fit specific applications

Cost-Savings that Other SSD Lines Cannot Deliver

- Alternative flash options provide a greater spectrum of price per IOPS
- Support for next generation NAND flash geometries

KEY DIFFERENTIATORS:

- Highest performing SSD in its class
- Ultra-high endurance for enterprise applications (increases drive life by up to five times the rated P/E cycles of the NAND flash)
- Unique ability to customize form factor, functionality (i.e. firmware), & components
- Robust feature-set including enterpriseclass ECC, data reliability, data path parity protection, and power fail protection

OCZ Deneva 2 SSDs are designed and manufactured to solve today's enterprise storage challenges and address the limitations hard drive technology imposes on IT infrastructures. The Deneva 2 Series delivers the industry's best performance while meeting the stringent reliability, security, and economical needs of enterprise storage environments including cloud storage, web-serving, and data warehousing. Providing a lucrative option for datacenters, Deneva 2 maximizes IOPS per dollar enabling increased data throughput with lower power consumption and a smaller operating footprint.

enterprise

OCC enterprise Deneva 2 R SLC Series Specifications

PHYSICAL						
Usable Capacities (IDEMA)	50GB ~ 200GB	50GB ~ 200GB				
NAND Components	Toggle-Mode Sine	Toggle-Mode Single-Level Cell (SLC)				
nterface	Serial ATA (SATA) 6Gb/s					
Form Factor	2.5 inch					
NAND Controller	SandForce® 2581/2582					
Dimensions (L x W x H)	100 x 69.75 x 9.2 mm					
Weight	83g (may vary slightly due to capacity)					
PERFORMANCE						
Max Read	up to 550 MB/s					
Max Write	up to 530 MB/s					
Random Read Operations (4kB)	up to 70,000 IOPS					
Random Write Operations (4kB)	up to 80,000 IOPS	up to 80,000 IOPS				
ENVIRONMENTAL						
Power Consumption	Idle: 1.3 Watts Active: 2.85 Watts					
Ambient Temperature	$0^{\circ}C \sim 55^{\circ}C$					
Operating Temperature	0°C ~ 70°C					
Storage Temperature	-45°C ~ 85°C					
Certifications	RoHS, CE, FCC					
RELIABILITY/SECURITY						
MTBF	10 million hours					
Data Fail Recovery	Recovers data from up to one NAND flash block					
Data Path Protection	ECC: Up to 55 bits correctable per 512-byte sector					
Data Reliability	Read Unrecoverable Bit Error Rate (UBER) 10e-17					
Data Encryption	128-bit AES-compliant					
Product Health Monitoring	Self-Monitoring, Analysis and Reporting Technology (SMART) Support w/ enterprise attributes					
COMPATIBILITY						
Serial ATA	Fully compliant with Serial ATA International Organization: Serial ATA Revision 3.0. Fully compliant with ATA/ATAPI-8 Standard Native Command Queuing (NCQ)					
Operating Systems	Windows XP 32-bit / 64-bit; Windows Vista 32-bit / 64-bit; Windows 7 32-bit / 64-bit; Linux; Mac OS X					
Power Requirements	Standard SATA Power Connector					
ADDITIONAL FEATURES						
Performance Optimization	TRIM (requires OS support)					
Service & Support	3-Year Warranty;	Dedicated F	AE/FSE support (includes PM/	engineer support through v	alidation cycle)	
PRODUCT		CAPACITY			ORDERING	
NAME TYPE	RAW ID	DEMA	WRITE ENDURANCE	PART NUMBER	UPC	
Deneva 2 R 2.5" SLC		0GB	Up to 50PB	D2RSTK251S14-0050	84202402929	
Deneva 2 R 2.5" SLC		00GB	Up to 100PB	D2RSTK251S14-0100	84202402995 84202402896	
Deneva 2 R 2.5" SLC	256GB 20	00GB	Up to 200PB	D2RSTK251S14-0200	04202402090	

© 2011 OCZ Technology Group, Inc. All rights reserved.